



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2002005614 A**(43) Date of publication of application: **09.01.02**

(51) Int. Cl.

G01B 9/02**G01B 11/02****G02F 1/11****H01S 5/12****H01S 5/14**(21) Application number: **2000188006**(22) Date of filing: **22.06.00**(71) Applicant: **MITSUBISHI HEAVY IND LTD**(72) Inventor: **ISHIOKA MASATO****(54) OPTICAL FREQUENCY MODULATION METHOD RANGE FINDER**

frequency shift, resulting in feedback to the semiconductor laser 20.

(57) Abstract:

COPYRIGHT: (C)2002,JPO

PROBLEM TO BE SOLVED: To provide an optical frequency modulation method range finder where an FSF light-source configuration is simplified for reducing cost, while degradation in sensitivity caused by the conventional multi-mode oscillation is prevented.

SOLUTION: A laser resonator comprises a rear end surface 28 of a semiconductor laser 20 and a mode selector element 27. The optical output from the semiconductor laser 20 is guided into an acousto-optical element 23 via a lens 26, and ultrasonic wave 30 is excited in the acoustic optical element 23, when applied with signal f_0 from an AOM modulating signal source 22. At the acoustic optical element 23, Bragg diffraction phenomenon occurs to split it into zeroth-order beam 25 and first-order diffracted beam 24, with the first-order diffracted beam 24 being outputted while deviating by f_0 in optical frequency due to the Doppler frequency shift. The first-order diffracted beam 24 has Fabry-Perot resonator condition, which only reflects arbitrary one oscillation mode component with the mode selector element 27, whose reflection leads it into the acousto-optical element 23 to undergo the Doppler

